

MR. COFFEE®

BVMC-KG2

Quick Start Guide

www.mrcoffee.com

Refer to Manual for Important Safeguards and Cleaning Instructions.



Step
1



Place Brewer upright on a flat surface and remove protective sheet and plug into outlet.

Step
3



Place chosen K-Cup into the K-Cup Assembly Housing. **CAUTION: Avoid the sharp needles in the K-Cup Assembly Housing.**

Step
2



DO NOT remove or puncture the foil lid of the K-Cup® portion pack.

Lift front handle of the brewer to insert a K-Cup.

Step
4



Lower the front handle completely and firmly to close the Lid and puncture the K-Cup portion pack.

Step
5



Depress the water marking button and the hot water tank will open automatically.

Step
8



Place a coffee cup on the dispense area on the drip tray. Press the BREW NOW button.
NOTE: Drip Tray can be removed to accommodate larger mugs.

Step
6



Fill the Hot Water tank with filtered or bottled water up to the FILL LEVEL indicator.
Note: Any spills outside the fill area will flow to the drip tray.

Step
9



When the water reaches temperature, the HEATING light will go off and the BREWING light will turn on.
NOTE: Pump will remain on for up to 90 seconds to complete brewing and drying the K-Cup.

Step
7



Close the Hot Water Tank cover.

Step
10



Enjoy!