

MR. COFFEE®

BVMC-KG1

Quick Start Guide

www.mrcoffee.com



- 1 Brew Now / Off
- 2 Heating Indicator (Red)
- 3 Brewing Indicator (Green)
- 4 Drip Tray Plate
- 5 Drip Tray
- 6 Lift Handle & Insert K-Cup® portion pack
- 7 Hot Water Tank



Step 1



Place Brewer upright on a flat surface and remove protective sheet and plug into outlet.

Step 3



Place chosen K-Cup into the K-Cup Assembly Housing. **CAUTION: Avoid the sharp needles in the K-Cup Assembly Housing.**

Step 2



DO NOT remove or puncture the foil lid of the K-Cup® portion pack.
Lift front facing of the brewer to insert a K-Cup.

Step 4



Lower the front facing completely and firmly to close the Lid and puncture the K-Cup portion pack.

Step
5



Depress the water marking button and the hot water tank will open automatically.

Step
8



Place a coffee cup in the dispense area on the drip tray. Press the BREW NOW button.

NOTE: Drip Tray can be removed to accommodate larger mugs.

Step
6



Fill the Hot Water tank with filtered or bottled water up to the FILL LEVEL indicator.

Step
9



When the water reaches temperature, the HEATING light will go off and the BREWING light will turn on.

NOTE: Pump will remain on for up to 90 seconds to dry the K-Cup.

Step
7



Close the Hot Water Tank cover.

Step
10



Enjoy!